

RX Spider

 ACCUREX



Low profile scale with ramps

With only 35 mm height and integrated ramps, for weighing trolleys and shelves with wheels.

- Extra flat platform with 4 load sensors.
- Installation on the ground, with ramps integrated into the weighing surface.
- 5 mm thick teardrop sheet, with epoxy treatment.
- OIML R-60 class C load cells in nickel steel with IP67 protection.
- With RX LED display and 400 cm long cable.
- Height adjustable feet to adapt it to the use surface.

The Accurex RX Spider scale models are products for professional use, they can withstand hard and intensive treatment. They are manufactured with a lacquered steel structure and a highly reliable RX electronic indicator.

The RX indicator with 4 metres of cable length can be placed at a distance from the platform. The response of the weighing is extremely fast, in less than 2 seconds it shows the stable weight accurately.





Operational functions

- Setting to zero.
- Taring of receptacles with tare memory.

It is powered by a 220V network and also by its internal battery, which is recharged by the same network cable. While the scale is being used, its battery is being recharged simultaneously.

Zero adjustment function. The unit can be zeroed at the press of a key

Tare function. The weight of a trolley, empty shelf or any other container can be deducted by pressing the tare key.

Calibration as standard. The equipment is supplied duly calibrated and adjusted by our calibration laboratory located in Barcelona (audited annually by the European notified body NMI).

Technical features

Model	RX Spider 88-300	RX Spider 88-600	RX Spider 1010-300	RX Spider 1010-600	RX Spider 1212-600	RX Spider 1212-1.5T
Reference	71757	71758	71759	71760	71761	71762
Capacity	300 kg	600 kg	300 kg	600 kg	600 kg	1500 kg
Resolution	50 g	100 g	50 g	100 g	100 g	200 g
Weighing units	kg					
Power	Network 220V 50 Hz					
Working temperature	0°C / +40°C					
Structure	Steel with epoxy paint in the oven					
Load Sensors	4 units H8C Rebel					
Junction box	ABS with IP65 protection					
Sheet metal thickness (mm)	5					
Dim. weighing area (mm)	800x800		1000x1000		1200x1200	
Dim. weighing area with ramps (mm)	800x1100		1000x1300		1200x1500	
Total dimensions (mm)	1100x1000x110		1300x1200x110		1500x1400x110	
Height (mm)	35					
Platform net weight (kg)	92		122		142	
Packing dimension (mm)	1110x1010x120		1310x1210x120		1510x1410x120	
Total weight with packaging (kg)	110		140		165	
PVP (€)	515,00	515,00	545,00	545,00	605,00	605,00

External dimensions (mm)

