

# series ZFOC



## ZFOC connectivity and versatility for your business.

- Connection to POS (RS model).
- USB connection ideal for PC (RS model).
- Long battery life thanks to its low power consumption.
- Dual front/backlit LCD display.
- OIML Approval.



Dual front/backlit LCD display

### Technical characteristics

Model	ZFOC-15	ZFOC-30	ZFOC-15P	ZFOC-30P	ZFOC-30 RS	ZFOC-30P RS
Reference	60631	60566	60632	60567	60564	60565
Capacity	6/15 Kg	15/30 kg	6/15 Kg	15/30 kg		
Readability	2/5 g	5/10 g	2/5 g	5/10 g		
Data output					RS 232-C	
Column	No		Yes		No	Yes
Power	3 AA batteries				USB power or 3 AA batteries	
Battery life	5000 hours/20 months				5000 hours/20 months	
Weighing units	kg, lb					
Structure material	ABS					
Pan size (mm)	230 x 330					
External dimensions (mm)	340 x 340 x 115		340 x 375 x 485		340 x 340 x 115	340 x 375 x 485
Total net weight (kg)	3,8					

## Main functions

### Metrological characteristics

- Capacities 6/15 kg and 15/30 kg multi-range
- Readability 2/5g and 5/10g

### Display

- 5 Digits for weight
- 7 Digits for unit price
- 8 Digits for total price

### Technical specifications

Low power consumption.

Power: 3 AA batteries or USB power (RS model).

Duration: 5000 horas/20 months



#### Stainless steel pan

Easy to clean, size 330x230mm.

#### Operational functions

- Auto power-off function.
- Manual tare.
- 5 direct PLUs.
- Accumulation of weights.
- Change function (RS model).
- Fixed-price function for all weights (RS model).

The ZFOC series has several models available in order to suit all needs.



### Better visibility

The column version of the ZFOC-P is equipped with a rear display for a better view.






### Total connectivity: USB

The ZFOC RS and ZFOC-P RS are equipped with a RS-232C output with USB adapter that lets you comfortably connect both your PC and your POS.



### External dimensions (mm)

#### ZFOC-15/30/30 RS Series



#### ZFOC-15P/30P/30P RS Series

